

Claims:

1 1. A system to initiate, by a host, an event in a first device, the system comprising:
2 a signal line to communicate a plurality of data values between a host and one or more
3 second devices; and
4 a tap line to communicate said plurality of data values between said signal line and said
5 first device;
6 wherein said event is initiated upon detection, by said first device, of a predetermined
7 sequence of data values on the tap line.

09883105-062221
1 2. The system of claim 1, wherein the event comprises a switching from a communication
2 path between the first device and a third device and a communication path between the signal
3 line and the third device.

1 3. The system of claim 1, wherein the event comprises a switching from a communication
2 path between a signal line and a third device and a communication path between the first device
3 and the third device.

1 4. The system of claim 1, wherein the host is a processor.

1 5. The system of claim 1, wherein the first device is a logic device.

1 6. The system of claim 1, wherein each of the one or more second devices is a memory
2 device.

1 7. The system of claim 1, wherein the third device is a memory device.

1 8. The system of claim 1, wherein the host is a microprocessor chipset, the first device is a
2 Field Programmable Gate Array (FPGA), each of the one or more second devices is a Dual In-
3 line Memory Module (DIMM), and the third device is Synchronous Dynamic Random Access
4 Memory (SDRAM).

1 9. The system of claim 1, wherein each of the plurality of data values represents a memory
2 location within any of the plurality of second memory devices.

1 10. The system of claim 9, wherein utilization of a data value provides a call to the
2 represented memory location.

1 11. A method to initiate, by a host, an event in a first device comprising:
2 communicating, by a signal line, a plurality of data values between a host and one or
3 more second devices;
4 communicating, by a tap line, said plurality of data values between said signal line and
5 said first device; and
6 initiating said event upon detection by said first device of a predetermined sequence of
7 data values on the tap line.

1 12. The method of claim 11, wherein the event comprises a switching from a communication
2 path between the first device and a third device and a communication path between the signal
3 line and the third device.

1 13. The method of claim 11, wherein the event comprises a switching from a communication
2 path between a signal line and a third device and a communication path between the first device
3 and the third device.

1 14. The method of claim 11, wherein the host is a processor.

1 15. The method of claim 11, wherein the first device is a logic device.

1 16. The method of claim 11, wherein each of the one or more second devices is a memory
2 device.

1 17. The method of claim 11, wherein the third device is a memory device.

1 18. The method of claim 11, wherein the host is a microprocessor chipset, the first device is a
2 Field Programmable Gate Array (FPGA), each of the one or more second devices is a Dual In-
3 line Memory Module (DIMM), and the third device is Synchronous Dynamic Random Access
4 Memory (SDRAM).

1 19. The method of claim 11, wherein each of the plurality of data values represents a memory
2 location within any of the plurality of second memory devices.

1 20. The method of claim 19, wherein utilization of a data value provides a call to the
2 represented memory location.

1 21. A set of instructions residing in a storage medium, said set of instructions capable of
2 being executed by a processor to initiate, by a host, an event in a first device comprising:
3 communicating, by a signal line, a plurality of data values between a host and one or
4 more second devices;
5 communicating, by a tap line, said plurality of data values between said signal line and
6 said first device; and
7 initiating said event upon detection by said first device of a predetermined sequence of
8 data values on the tap line.

1 22. The set of instructions of claim 21, wherein the event comprises a switching from a
2 communication path between the first device and a third device and a communication path
3 between the signal line and the third device.

1 23. The set of instructions of claim 21, wherein the event comprises a switching from a
2 communication path between a signal line and a third device and a communication path between
3 the first device and the third device.

